

# ENGINE DRIVEN WELDERS



## Miller BOBCAT 250 NT ENGINE-DRIVEN WELDER

UNLEASH MORE POWER! This moderately priced engine drive delivers 250 amps of AC or DC weld output for greater deposition rates and faster travel speeds. It is a rugged and reliable workhorse that sets the standard for stick and FCAW welding. With the highest auxiliary power output in its class – 10,000 watts – it allows you to simultaneously weld while running power tools and lights.

**PROCESSES:**

- AC/DC stick (SMAW).
- Flux cored (FCAW).
- MIG (GMAW).
- DC TIG (DC GTAW).
- Non-critical AC TIG (GTAW).
- Air plasma cutting and gouging (PAC) with optional spectrum models.
- Air carbon arc (CAC-A) cutting and gouging (3/16 in carbons).

**INDUSTRIAL APPLICATIONS:**

- Fabrication.
- Structural steel work.
- Maintenance.
- Farm and ranch.
- Use as stand alone generator.

**SPECIFICATIONS:**

Stock Number ..... (#903 810) Kohler, 20 HP at 3600 RPM  
 Welding Mode ..... CC/AC, CC/DC, CV/DC  
 Process ..... Stick TIG, MIG/FCAW  
 Amp/Volt Ranges ..... 40–100A, 60–140A, 80–200A, 100–250A, 17–22V, 20–28V  
 Rated Output at 104°F (40°C) ..... 250A at 25V, 100% duty cycle, 250A at 28V, 100% duty cycle  
 Auxiliary Power ..... Peak: 10,000 watts, continuous: 9500 watts, 84/42A 120/240 VAC, 60 Hz  
 Size ..... 33H x 18-3/4W x 45-1/2"D.

Mfg. No. 903-810  
 Model 6583 0060T  
**\$3,661<sup>35</sup>**  
 Wt. 519 lbs.



**OPTIONAL ACCESSORIES**

Model	Mfg. No.	Description	Price
6583 0070	041930	<b>No. 4B Running Gear</b> For Blue Charger NT, Bobcats, Miller Legend NT and Trailblazers	<b>303.45</b>
6583 0072	043040	<b>Cylinder Rack</b> For Use with No. 4B or No. 27 Running Gear	<b>182.70</b>
6583 0074	040039	<b>No. 2WA Welding Accessories</b> Includes 35 ft. (10.7m) No. 2/0 Electrode Cable with Insulated Electrode Holder and Lug, 30 Ft. (9.1m) No. 2/0 Work Cable with Clamp and Lug, Welding Helmet, and Wire Scratch Brush	<b>238.35</b>
6583 0076	194890	<b>Suitcase 8 VS Wire Feeder</b> At Less Than 25 lb. and Fits Through 18 x 24 in. Porthole	<b>1,352.40</b>
6583 1410	130831	<b>Spoolmatic® 30A Spool Gun</b> Ideal for Aluminum Welding Jobs, 200 amp, 100% Duty Cycle, Air-Cooled, 1 lb. Spool Gun with 30 ft. (9.1m) Cable Assembly	<b>1,044.75</b>
6583 0078	043857	<b>SGA 100C Control with Contactor</b> The SGA Contactor is Required to Connect a Spoolmate™ Spool Gun to CV Engine Drives like Miller's Bobcat™. Includes 10 ft. (3m) 115 VAC Power Cable and Plug, 6 ft. (1.8m) Interconnecting Cable, and a 5 ft. (1.5m) Gas Hose	<b>271.95</b>
6583 0080	043579	<b>Spark Arrestor</b> Mandatory when Operating on California Grasslands, Brush or Forest-Covered Land, and All National Forests. For Other Areas, Check Your State and Local Laws	<b>40.95</b>
6583 0082	043674	<b>Canvas Cover CC-1A1 (with Miller Logo)</b> For Blue Charger NT, Bobcats, Miller Legend NT, and Trailblazers. 26H x 21W x 49"L	<b>103.95</b>

## GOWELD™ PORTABLE MIG WELDER KIT

**FEATURES:**

- 24V or 36V battery power – 200 amps.
- Welds steel and aluminum from 1/8 to over 1/2" thick.
- Weld with shielding gas or gasless wires.
- Up to 20 minutes arc-time on 2 batteries.
- Computer controlled functions.
- Microprocessor wire speed controller.
- Programmed microprocessor to monitor feed and weld functions.
- Accommodates 2 lb. (1 kg.) spools of steel or aluminum solid (MIG/MAG) or flux core self shielding (FCAW) wire from .023–.045 diameters to weld material up to 1" thick.

**New!**



**INCLUDES:**

- GOWELD with power cable (20').
- Ground cable (20').
- Gas line (20') w/inert gas "B" fitting.
- Battery cable harness, battery jumper cable.
- .030" contact tips (3 ea.).
- .035" contact tips (3 ea.).
- .035" ER70S-6 wire electrode (1 spool).
- .035" E71T-GS wire electrode (1 spool).
- 1 nozzle.
- Operating manual.
- Rugged storage case.



**Generates up to 200 AMPS using two 12-Volt Deep Cycle Batteries!**

**GO-WELD PORTABLE BATTERY WELDER**  
 Model 6583 9000  
**\$795<sup>20</sup>**

12-VOLT BATTERIES NOT INCLUDED